

## caratteristiche tecniche technical features carateristiques techniques technische eigenschaften

	ISO 10545-3	assorbimento d'acqua water absorption	<0.5%		UNI EN 101	durezza di Mohs hardness in Mohs degrees	≥ 7
	ISO 10545-4	resistenza alla flessione breaking strength	35 N/mm <sup>2</sup>			spessore thickness	9.5 mm
	ISO 10545-13	resistenza agli acidi resistance to acid	GLA		DIN 51097 DIN 51130	coefficiente d'attrito (scivolosità) static coefficient of friction	A+B R10
	ISO 10545-12	resistenza al gelo frost resistance	resiste frost proof		DCOF BOT 3000		> 0.42
	ISO 10545-14	resistenza alle macchie stain resistance	5			variazioni cromatiche color shade variations	V2 variazione leggera V2 slight variation
	ISO 10545-2	planarità surface flatness	±0.5%				

## imballi packing embalages verpackung

formato size		spessore thickness	pezzi/sc pcs/box	mq/sc sqm/box	kg/sc kgs/box	sc/pl box/pal	mq/pl sqm/pal	kg/pl kgs/pal
61.5x61.5	naturale	9.5	4	1.51	30.50	30	45.30	915.00
30.8x61.5	naturale	9.5	7	1.32	26.65	40	52.80	1066.00
30.8x30.8	mosaico		11	1.04	19.70	54	56.16	1063.80
30.8x61.5	murales		5		17.90			
7x61.5	battiscopa smaltato		12		12.60			
30.8x61.5	gradino naturale e grip		8		33.84			
30.8x61.5	elemento a L naturale e grip		4		17.20			

**il peso riportato è comprensivo del pallet di supporto**  
 the indicated weight includes the supporting pallet  
 le poids indiquè est compris de la palette de support  
 das angegebene gewicht versteht sich einschließlic der palette